

K388Pro

Mobile Labeling Printer

- Ultra-compact 4-in-1 Design**
 Integrated scanning, printing, peeling & labeling in a single device.
 Achieve full labeling process in just 1.5 seconds for unmatched speed and precision.
- Professional-grade scanning engine with millisecond decoding speed**
 Support 1D/2D codes scanning and printing, effortlessly replacing damaged or creased labels with greater speed and accuracy
- High-performance data terminal**
 Equipped with an Octa-core 2.4GHz Android terminal and a 5.5-inch large screen display for seamless and convenient operation
- Precision narrow-width printing**
 Providing 2" (50.8mm) professional printing width with 120mm/s ultra-fast speed. Quick-release paper magazine for forward/reverse label rolls.



1D/2D Barcodes
Scanning



Print Speed - Up to
120 mm/s



Resolution: 203dpi
(8 μ m / mm)



Automatic Label
Peeling



5.5-inch
Display



10.8V/3000mAh
(32.4Wh), support

K388Pro Mobile Labeling Printer

Specifications

UROVO

Printing Features

Thermal direct
Print Width ≤ 58mm
Paper thickness: 50 ~ 180µm
Printing speed (max.): Up to 120mm/s
Supply roll diameter: ≤ 60mm
Supply roll thickness: 50 ~ 180µm

Scanning

Professional scan engine,
support international standard 1D/2D
barcodes

Command Set

CPCL, ZPL, TSPL

CPU

Octa-core 2.4 GHz

O.S.

Android 14.0

Memory

RAM: 4GB, ROM: 64GB

Dimensions

Size: 185mm × 85mm × 137mm
Weight: 800g

Display

5.5 inch display
720*1440

Power Supply

Battery: 32.4Wh (3000mAh) /10.8V
rechargeable lithium-ion battery
Charging: Charged directly or through the battery
Inches per charge: Up to 200 meters (12.5% black printing)
Adapter: 5V 2A
support hot-swap

Communication

Bluetooth: Class 2, Bluetooth v5.3 and
secondary BLE
Wi-Fi: 2.4G/5G
IEEE: 802.11a/b/g/n/ac/d/h/i/k/r/v/w/mc/ax
Support Wi-Fi 6E, support 2x2 MU-MIMO
Audio: Microphone*1, Speakers*1
Camera: Front 5MP, Rear 13MP with flash

Environmental

Working temperature: -20°C ~ +60°C
Storage temperature: -40°C ~ +70°C
Operating humidity (relative humidity): 5% ~ 95%
Drop Specification: Multiple 5 ft./1.5 m drop to
concrete at room temperature
ESD: +/-15kv Air; +/-8kv contact

UROVO PTE. LIMITED

Website: en.urovo.com

Email: urovo@urovo.com

Address: 1 Raffles Place, #21-01 One Raffles Place Tower 1,
Singapore 048616

*This page is subject to change
without prior notice